4A 4Quadrants TRIACs

Product Summary

Symbol	Value	Unit

Features

Application


Absolute maximum ratings (Ta=25°C unless otherwise noted)


Parameter	Symbol	Value	Unit
	V_{DRM}		
	V_{RRM}		
	$I_{T(RMS)}$		
	I_{TSM}		
	I^2t		

Electrical characteristics (T_A=25°C, unless otherwise noted)

Parameter	Symbol	Test Condition	Value	Unit

STATIC CHARACTERISTICS


5
4
3
2
1
0
0
1
2
3
4



	TO-220F	0.06oz(1.74g)	50pcs/tube	1000PCS/Box 5000PCS/Carton

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales office for further assistance.