
3-terminal 3.3V 0.1A positive voltage regulator

Description

Features



Marking Code	
78L33S	YFW 78L33S

Internal Block Digram



Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Input voltage	V_{IN}	20	V
Output current	I_{OUT}	100	mA

Electrica

Typical Characteristics




Fig1 .Output Voltage vs AmbientTemperature




Figure 2. Quiescent Current vs Output Current




Figure 3 : Load Characteristics






Figure 4 : Quiescent Current vs Input Voltage



Marking Diagram




Ordering information

Package	Packing Description	Packing Quantity
SOP-8	Tape/Reel,13”reel	3000PCS/Reel 30000PCS/Carton


Package Dimensions

SOP-8



	Min.	Max.	Min.	Max.
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
A2	1.35	1.50	0.053	0.059
b	0.35	0.55	0.014	0.022
c	0.15	0.25	0.006	0.010
D	4.80	5.00	0.189	0.197
D1	3.10	3.50	0.122	0.138
E	5.80	6.20	0.228	0.244
E1	3.80	4.00	0.150	0.157
E2	2.20	2.60	0.087	0.102
e	1.27 (BSC)		0.050 (BSC)	
L	0.40	1.27	0.016	0.050
θ	0°	8°	0°	8°

The recommended mounting pad size



The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used